

# Prestige Security Doors: Technical Information

## **Gardesa Security Doors Specifications**

ANTI-BURGLARY CERTIFICATION EUROPEAN STANDARD UNI ENV 1627 TESTED FOR RESISTANCE TO STATIC LOAD, DYNAMIC LOAD AND MANUAL ATTACK WITH HAND TOOLS

### **Class Two**

- Constructed of 1.2mm thick steel
- Two part steel frame of 1.5mm thick steel
- Main lock with latch plus three bolts
- Top and bottom single dead bolts
- Hinge bolts
- Adjustable hinges
- Spyhole
- Single key operation by europrofile cylinder

### **Class Three**

- Constructed of 1.8mm thick steel
- Two part steel frame of 1.5mm thick steel
- Main lock with latch plus three bolts
- Top and bottom double dead bolts
- Three hinge bolts
- Adjustable hinges
- Spyhole
- Single key operation by europrofile cylinder
- Fire resistant insulation panel
- Mobile drop sill
- Safety catch

### **Contact:**

William Reid

e: [info@prestigesecuritydoors.ie](mailto:info@prestigesecuritydoors.ie)

m: (087) 664-88-48 | (087) 962-94-40

w: [www.PrestigeSecurityDoors.ie](http://www.PrestigeSecurityDoors.ie)